

SHADES - SUMMER FLOWERS (MD)

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 18/03/2024 Version: 10.45

Generated: 27/04/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture

Trade name : SHADES - SUMMER FLOWERS (MD)

UFI EUC3-S01Y-M003-CF66

Product code KSD1 Type of product : Aerosol Vaporizer : Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Professional use

Industrial/Professional use spec : For professional use only

Use of the substance/mixture : Air Freshener

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SELDEN RESEARCH LIMITED

STADEN LANE BUXTON DERBYSHIRE SK17 9R7 UNITED KINGDOM

Tel: 01298 26226 Email: safety@selden.co.uk

SELDEN EUROPE B.V.

WATERMOLEN 13 6229 PM MAASTRICHT **NEDERLAND**

Tel: +31 (0) 43 363 42 89 Email: sds@selden.eu

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229 Serious eye damage/eye irritation, Category 2 H319

Full text of H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

Document generated @ 27/04/2024 18:10:51 Page 1 of 11

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)





GHS02

GHS07

Signal word (CLP)

Precautionary statements (CLP)

: Danger

Hazard statements (CLP) : H222 - Extremely flammable aerosol.

H229 - Pressurised container: May burst if heated.

H319 - Causes serious eye irritation. : P102 - Keep out of reach of children.

P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources.

No smoking.

P211 - Do not spray on an open flame or other ignition source.

P251 - Do not pierce or burn, even after use. P264 - Wash hands thoroughly after handling.

P280 - Wear eye protection.

P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove

contact lenses, if present and easy to do. Continue rinsing. P337+P313 - If eye irritation persists: Get medical advice/attention.

P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. EUH208 - Contains Benzyl salicylate, Hexyl cinnamic aldehyde. May produce an allergic

reaction.

EUH-statements

2.3. Other hazards

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane substance with national workplace exposure limit(s) (IE, GB)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691- 32	30 – 60	Flam. Gas 1A, H220 Press. Gas
propane substance with national workplace exposure limit(s) (IE)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944- 21	15 – 30	Flam. Gas 1A, H220
isobutane substance with national workplace exposure limit(s) (IE)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395- 27	15 – 30	Flam. Gas 1A, H220 Press. Gas

Document generated @ 27/04/2024 18:10:51

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (IE, GB)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558- 25	10 – 15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Benzyl salicylate	CAS-No.: 118-58-1 EC-No.: 204-262-9	0.1 – 1	Skin Sens. 1, H317
Hexyl cinnamic aldehyde	CAS-No.: 101-86-0 EC-No.: 202-983-3 REACH-no: 01-2119533092- 50	0.1 – 1	Skin Sens. 1B, H317 Aquatic Acute 1, H400 (M=1) Aquatic Chronic 2, H411

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general : Get medical advice/attention if you feel unwell.

First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. First-aid measures after skin contact : Wash skin with plenty of water. Take off contaminated clothing.

First-aid measures after eye contact : Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

First-aid measures after ingestion : Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Get medical advice/attention.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects : Not expected to present a significant hazard under anticipated conditions of normal use.

Symptoms/effects after inhalation : High concentration of vapours may induce: headache, nausea, dizziness.

Symptoms/effects after skin contact : Repeated exposure may cause skin dryness or cracking.

Symptoms/effects after eye contact : Causes eye irritation.

Symptoms/effects after ingestion : May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media : Carbon dioxide. Dry powder. Foam.

5.2. Special hazards arising from the substance or mixture

Fire hazard : Extremely flammable aerosol. Explosion hazard : Explosion risk in case of fire.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources.

Document generated @ 27/04/2024 18:10:51

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

6.1.2. For emergency responders

Protective equipment : Use personal protective equipment as required.

6.2. Environmental precautions

Avoid release to the environment.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Do not pierce or burn, even after use.

Precautions for safe handling : Do not spray on an open flame or other ignition source. Hygiene measures : Do not eat, drink or smoke when using this product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Does not require any specific or particular technical measures.

Storage conditions : Keep away from ignition sources. Protect from sunlight. Do not expose to temperatures

exceeding 50°C/122°F.

Incompatible products : Oxidizing agent. Strong acids. Strong bases.
Incompatible materials : Direct sunlight. Heat sources. Sources of ignition.

Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

propane (74-98-6)		
Ireland - Occupational Exposure Limits		
Local name	Propane	
OEL TWA [2]	1000 ppm	
Remark	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)	
Regulatory reference	Chemical Agents Code of Practice 2020	
isobutane (75-28-5)		
Ireland - Occupational Exposure Limits		
Local name	Butane, all isomers: Isobutane	
OEL STEL 1000 ppm		

Document generated @ 27/04/2024 18:10:51 Page 4 of 11

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

isobutane (75-28-5)			
Regulatory reference	Chemical Agents Code of Practice 2020		
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)			
Ireland - Occupational Exposure Limits	Ireland - Occupational Exposure Limits		
Local name	Isopropyl alcohol		
OEL TWA [2]	200 ppm		
OEL STEL	400 ppm		
Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018		
United Kingdom - Occupational Exposure Limits			
Local name	Propan-2-ol		
WEL TWA (OEL TWA) [1]	999 mg/m³		
WEL TWA (OEL TWA) [2]	400 ppm		
WEL STEL (OEL STEL)	1250 mg/m³		
WEL STEL (OEL STEL) [ppm]	500 ppm		
Regulatory reference	EH40/2005 (Third edition, 2018). HSE		
butane (106-97-8)			
Ireland - Occupational Exposure Limits			
Local name	Butane		
OEL TWA [2]	1000 ppm		
OEL STEL	1000 ppm		
Regulatory reference	Chemical Agents Code of Practice 2020		
United Kingdom - Occupational Exposure Limits			
Local name	Butane		
WEL TWA (OEL TWA) [1]	1450 mg/m³		
WEL TWA (OEL TWA) [2]	600 ppm		
WEL STEL (OEL STEL)	1810 mg/m³		
WEL STEL (OEL STEL) [ppm]	750 ppm		
Remark	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

Document generated @ 27/04/2024 18:10:51 Page 5 of 11

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection:

Safety glasses

8.2.2.2. Skin protection

Skin and body protection:

Not required for normal conditions of use

Hand protection:

In case of repeated or prolonged contact wear gloves

Other skin protection

Materials for protective clothing:

Not required for normal conditions of use

8.2.2.3. Respiratory protection

Respiratory protection:

Not required for normal conditions of use

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid Colour Colourless. Appearance Aerosol. Odour : Floral. : Not available Odour threshold Melting point : Not available Freezing point : Not available : Not available Boiling point Flammability : Not available Explosive limits : Not available Lower explosive limit (LEL) : Not available Upper explosive limit (UEL) : Not available Flash point : Not applicable Auto-ignition temperature : Not available Decomposition temperature : Not available рΗ : Not available Viscosity, kinematic : Not available Solubility : Not available Partition coefficient n-octanol/water (Log Kow) : Not available : Not available Vapour pressure Vapour pressure at 50°C : Not available Density : Not available : 0.6 Relative density

Particle size : Not applicable

: Not available

Document generated @ 27/04/2024 18:10:51

Relative vapour density at 20°C

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Particle size distribution : Not applicable
Particle shape : Not applicable
Particle aspect ratio : Not applicable
Particle aggregation state : Not applicable
Particle agglomeration state : Not applicable
Particle specific surface area : Not applicable
Particle dustiness : Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients : 91.14400886

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Pressurised container: May burst if heated.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Direct sunlight. Heat. Open flame.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Not classified
Acute toxicity (dermal) : Not classified
Acute toxicity (inhalation) : Not classified
Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Causes serious eye irritation.

Respiratory or skin sensitisation : Not classified
Germ cell mutagenicity : Not classified
Carcinogenicity : Not classified
Reproductive toxicity : Not classified
STOT-single exposure : Not classified

propan-2-ol; isopropyl alcohol; isopropanol

STOT-single exposure May cause drowsiness or dizziness.

STOT-repeated exposure : Not classified Aspiration hazard : Not classified

Document generated @ 27/04/2024 18:10:51 Page 7 of 11

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Vaporizer	Aerosol

11.2. Information on other hazards

No additional information available

SECTION 12: Ecological information

12.1. Toxicity

Hazardous to the aquatic environment, short-term : Not classified

(acute)

Hazardous to the aquatic environment, long-term : Not classified

(chronic)

(China)		
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)		
LC50 - Fish [1] 9640 mg/l		
EC50 - Other aquatic organisms [1] 13299 mg/l waterflea		
EC50 - Other aquatic organisms [2]	> 1000 mg/l	
Hexyl cinnamic aldehyde (101-86-0)		
LC50 - Fish [1] 1.7 mg/l		
EC50 - Other aquatic organisms [2] > 0.32 mg/l		

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)		
Partition coefficient n-octanol/water (Log Pow) 0.05		
Hexyl cinnamic aldehyde (101-86-0)		
Partition coefficient n-octanol/water (Log Pow) 5.3		

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Endocrine disrupting properties

No additional information available

12.7. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Do not pierce or burn, even after use.

Document generated @ 27/04/2024 18:10:51 Page 8 of 1'

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 14: Transport information

In accordance with ADR / IMDG / IATA

14.1. UN number or ID number

UN-No. (ADR) : UN 1950 UN-No. (IMDG) : UN 1950 UN-No. (IATA) : UN 1950

14.2. UN proper shipping name

Proper Shipping Name (ADR) : AEROSOLS
Proper Shipping Name (IMDG) : AEROSOLS

Proper Shipping Name (IATA) : Aerosols, flammable

Transport document description (ADR) : UN 1950 AEROSOLS, 2.1, (D)
Transport document description (IMDG) : UN 1950 AEROSOLS, 2.1
Transport document description (IATA) : UN 1950 Aerosols, flammable, 2.1

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 2.1
Danger labels (ADR) : 2.1



IMDG

Transport hazard class(es) (IMDG) : 2.1
Danger labels (IMDG) : 2.1



IATA

Transport hazard class(es) (IATA) : 2.1
Danger labels (IATA) : 2.1



14.4. Packing group

Packing group (ADR) : Not applicable
Packing group (IMDG) : Not applicable
Packing group (IATA) : Not applicable

14.5. Environmental hazards

Dangerous for the environment : No Marine pollutant : No

Other information : No supplementary information available

14.6. Special precautions for user

Overland transport

Classification code (ADR) : 5F

Special provisions (ADR) : 190, 327, 344, 625

Limited quantities (ADR) : 1I

Document generated @ 27/04/2024 18:10:51 Page 9 of 11

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Excepted quantities (ADR) : E0

Packing instructions (ADR) : P207, LP200 Special packing provisions (ADR) : PP87, RR6, L2

Mixed packing provisions (ADR) : MP9
Transport category (ADR) : 2
Special provisions for carriage - Packages (ADR) : V14
Special provisions for carriage - Loading, unloading : CV9, CV12

and handling (ADR)

Special provisions for carriage - Operation (ADR) : S2 Tunnel restriction code (ADR) : D

Transport by sea

Special provisions (IMDG) : 63, 190, 277, 327, 344, 381, 959

Limited quantities (IMDG) : SP277

Excepted quantities (IMDG) : E0

Packing instructions (IMDG) : P207, LP200

Special packing provisions (IMDG) : PP87, L2

EmS-No. (Fire) : F-D

EmS-No. (Spillage) : S-U

Stowage category (IMDG) : None

Air transport

PCA Excepted quantities (IATA) : E0
PCA Limited quantities (IATA) : Y203
PCA limited quantity max net quantity (IATA) : 30kgG
PCA packing instructions (IATA) : 203
PCA max net quantity (IATA) : 75kg
CAO packing instructions (IATA) : 203
CAO max net quantity (IATA) : 150kg

Special provisions (IATA) : A145, A167, A802

ERG code (IATA) : 10L

14.7. Maritime transport in bulk according to IMO instruments

IBC code : Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:		
Aquatic Acute 1 Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 2 Hazardous to the aquatic environment – Chronic Hazard, Category 2		

Document generated @ 27/04/2024 18:10:51 Page 10 of 1'

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:		
EUH208	Contains Benzyl salicylate, Hexyl cinnamic aldehyde. May produce an allergic reaction.	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	
Flam. Gas 1A	Flammable gases, Category 1A	
Flam. Liq. 2	Flammable liquids, Category 2	
H220	Extremely flammable gas.	
H222	Extremely flammable aerosol.	
H225	Highly flammable liquid and vapour.	
H229	Pressurised container: May burst if heated.	
H317	May cause an allergic skin reaction.	
H319	Causes serious eye irritation.	
H336	May cause drowsiness or dizziness.	
H400	Very toxic to aquatic life.	
H411	Toxic to aquatic life with long lasting effects.	
Press. Gas	Gases under pressure	
Skin Sens. 1	Skin sensitisation, Category 1	
Skin Sens. 1B	Skin sensitisation, category 1B	
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis	

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1 H222;H229 On basis of test data		
Eye Irrit. 2	H319	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.

Document generated @ 27/04/2024 18:10:51 Page 11 of 11