

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830 Revision date: 18/03/2024 Version: 10.46

Generated : 27/04/2024

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form	: Mixture
Trade name	: SHADES - MARINE BREEZE (MD)
UFI	: 8XC3-80RC-W00K-1SS8
Product code	: KSD2
Type of product	: Aerosol
Vaporizer	: Aerosol

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category Industrial/Professional use spec Use of the substance/mixture

- : Professional use : For professional use only
- : Air Freshener

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

SELDEN RESEARCH LIMITED

STADEN LANE BUXTON DERBYSHIRE SK17 9R7 UNITED KINGDOM

Tel: 01298 26226 Email: safety@selden.co.uk

SELDEN EUROPE B.V. WATERMOLEN 13

6229 PM MAASTRICHT NEDERLAND

Tel: +31 (0) 43 363 42 89 Email: sds@selden.eu

1.4. Emergency telephone number

Country	Organisation/Company	Address	Emergency number	Comment
Ireland	National Poisons Information Centre Beaumont Hospital	PO Box 1297 Beaumont Road 9 Dublin	+353 1 809 2566 (Healthcare professionals- 24/7) +353 1 809 2166 (public, 8am - 10pm, 7/7)	
United Kingdom	National Poisons Information Service (Birmingham Centre) City Hospital	Dudley Road B18 7QH Birmingham	0344 892 0111	Only for healthcare professionals

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Aerosol, Category 1 H222;H229 Serious eye damage/eye irritation, Category 2 Hazardous to the aquatic environment - Chronic Hazard, Category 3 Full text of H- and EUH-statements: see section 16

H319 H412

Adverse physicochemical, human health and environmental effects

No additional information available

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.2. Label elements	
Labelling according to Regulation (EC)	No. 1272/2008 [CLP]
Hazard pictograms (CLP)	
	GHS02 GHS07
Signal word (CLP)	: Danger
Hazard statements (CLP)	: H222 - Extremely flammable aerosol.
	H229 - Pressurised container: May burst if heated.
	H319 - Causes serious eye irritation.
	H412 - Harmful to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P102 - Keep out of reach of children.
	P210 - Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211 - Do not spray on an open flame or other ignition source.
	P251 - Do not pierce or burn, even after use.
	P264 - Wash hands thoroughly after handling.
	P273 - Avoid release to the environment.
	P280 - Wear eye protection.
	P305+P351+P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove
	contact lenses, if present and easy to do. Continue rinsing.
	P337+P313 - If eye irritation persists: Get medical advice/attention.
EUH-statements	 P410+P412 - Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. EUH208 - Contains Benzyl salicylate, (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.

2.3. Other hazards

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or substance(s) are not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
butane substance with national workplace exposure limit(s) (IE, GB)	CAS-No.: 106-97-8 EC-No.: 203-448-7 EC Index-No.: 601-004-00-0 REACH-no: 01-2119474691- 32	30 – 60	Flam. Gas 1A, H220 Press. Gas
propane substance with national workplace exposure limit(s) (IE)	CAS-No.: 74-98-6 EC-No.: 200-827-9 EC Index-No.: 601-003-00-5 REACH-no: 01-2119486944- 21	15 – 30	Flam. Gas 1A, H220

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
isobutane substance with national workplace exposure limit(s) (IE)	CAS-No.: 75-28-5 EC-No.: 200-857-2 EC Index-No.: 601-004-00-0 REACH-no: 01-2119485395- 27	15 – 30	Flam. Gas 1A, H220 Press. Gas
propan-2-ol; isopropyl alcohol; isopropanol substance with national workplace exposure limit(s) (IE, GB)	CAS-No.: 67-63-0 EC-No.: 200-661-7 EC Index-No.: 603-117-00-0 REACH-no: 01-2119457558- 25	10 – 15	Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336
Benzyl salicylate	CAS-No.: 118-58-1 EC-No.: 204-262-9	0.1 – 1	Skin Sens. 1, H317
(R)-p-mentha-1,8-diene; d-limonene	CAS-No.: 5989-27-5 EC-No.: 227-813-5 EC Index-No.: 601-029-00-7 REACH-no: 01-2119529223- 47	0.1 – 1	Flam. Liq. 3, H226 Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Product subject to CLP Article 1.1.3.7. The disclosure rules of the components is modified in this case. Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures	
4.1. Description of first aid measures	
First-aid measures general First-aid measures after inhalation First-aid measures after skin contact First-aid measures after eye contact	 Get medical advice/attention if you feel unwell. Remove person to fresh air and keep comfortable for breathing. Wash skin with plenty of water. Take off contaminated clothing. Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Do NOT induce vomiting. Rinse mouth. Drink plenty of water. Get medical advice/attention.
4.2. Most important symptoms and effe	cts, both acute and delayed
Symptoms/effects Symptoms/effects after inhalation Symptoms/effects after skin contact Symptoms/effects after eye contact Symptoms/effects after ingestion	 Not expected to present a significant hazard under anticipated conditions of normal use. High concentration of vapours may induce: headache, nausea, dizziness. Repeated exposure may cause skin dryness or cracking. Causes eye irritation. May cause a light irritation of the linings of the mouth, throat, and gastrointestinal tract.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures		
5.1. Extinguishing media		
Suitable extinguishing media	: Carbon dioxide. Dry powder. Foam.	
5.2. Special hazards arising from the sub	stance or mixture	
Fire hazard Explosion hazard	Extremely flammable aerosol.Explosion risk in case of fire.	
5.3. Advice for firefighters		
Firefighting instructions	: Use water spray or fog for cooling exposed containers.	
Document generated @ 27/04/2024 18:12:35		Page 3 of 11

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

SECTION 6: Accidental release me	easures	
6.1. Personal precautions, protective equipment and emergency procedures		
General measures	: Remove ignition sources.	
6.1.1. For non-emergency personnel		
Emergency procedures	: Evacuate unnecessary personnel.	
6.1.2. For emergency responders		
Protective equipment	: Use personal protective equipment as required.	
6.2. Environmental precautions		
Avoid release to the environment.		
6.3. Methods and material for contain	ment and cleaning up	
For containment	: Collect spillage.	
Methods for cleaning up	: Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible.	
6.4. Reference to other sections		

For further information refer to section 8: "Exposure controls/personal protection". For further information refer to section 13.

SECTION 7: Handling and storage	
7.1. Precautions for safe handling	
Additional hazards when processed Precautions for safe handling Hygiene measures	 Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Do not eat, drink or smoke when using this product.
7.2. Conditions for safe storage, including	ng any incompatibilities
Technical measures Storage conditions	 Does not require any specific or particular technical measures. Keep away from ignition sources. Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F.
Incompatible products Incompatible materials Special rules on packaging	 Oxidizing agent. Strong acids. Strong bases. Direct sunlight. Heat sources. Sources of ignition. Keep only in original container.
7.3. Specific end use(s)	

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1 National occupational exposure and biological limit values

propane (74-98-6)		
Ireland - Occupational Exposure Limits		
Local name	Propane	
OEL TWA [2]	1000 ppm	
Remark	Asphx. (Gaseous chemical substances which may not produce significant physiological effects in the exposed employee, but when present in high concentrations will act as simple asphyxiants)	
Regulatory reference	Chemical Agents Code of Practice 2020	

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

isobutane (75-28-5)			
Ireland - Occupational Exposure Limits			
Local name	Butane, all isomers: Isobutane		
OEL STEL	1000 ppm		
Regulatory reference	Chemical Agents Code of Practice 2020		
propan-2-ol; isopropyl alcohol; isopropanol (6	67-63-0)		
Ireland - Occupational Exposure Limits			
Local name	Isopropyl alcohol		
OEL TWA [2]	200 ppm		
OEL STEL	400 ppm		
Regulatory reference	Code of Practice for the Chemical Agents Regulations 2018		
United Kingdom - Occupational Exposure Limits			
Local name	Propan-2-ol		
WEL TWA (OEL TWA) [1]	999 mg/m³		
WEL TWA (OEL TWA) [2]	400 ppm		
WEL STEL (OEL STEL)	1250 mg/m ³		
WEL STEL (OEL STEL) [ppm]	500 ppm		
Regulatory reference	EH40/2005 (Third edition, 2018). HSE		
butane (106-97-8)			
Ireland - Occupational Exposure Limits			
Local name	Butane		
OEL TWA [2]	1000 ppm		
OEL STEL	1000 ppm		
Regulatory reference	Chemical Agents Code of Practice 2020		
United Kingdom - Occupational Exposure Limits			
Local name	Butane		
WEL TWA (OEL TWA) [1]	1450 mg/m ³		
WEL TWA (OEL TWA) [2]	600 ppm		
WEL STEL (OEL STEL)	1810 mg/m ³		
WEL STEL (OEL STEL) [ppm]	750 ppm		
Remark	Carc, (only applies if Butane contains more than 0.1% of buta-1,3-diene)		
Regulatory reference	EH40/2005 (Fourth edition, 2020). HSE		

8.1.2. Recommended monitoring procedures

No additional information available

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

No additional information available

8.1.5. Control banding

No additional information available

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

8.2. Exposure controls

8.2.1. Appropriate engineering controls

No additional information available

8.2.2. Personal protection equipment

Personal protective equipment symbol(s):



8.2.2.1. Eye and face protection

Eye protection: Safety glasses

8.2.2.2. Skin protection

Skin and body protection: Not required for normal conditions of use

Hand protection: In case of repeated or prolonged contact wear gloves

Other skin protection

Materials for protective clothing: Not required for normal conditions of use

8.2.2.3. Respiratory protection

Respiratory protection: Not required for normal conditions of use

8.2.2.4. Thermal hazards

No additional information available

8.2.3. Environmental exposure controls

No additional information available

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	:	Liquid
Colour	:	Colourless.
Appearance	:	Aerosol.
Odour	:	Fresh.
Odour threshold	:	Not available
Melting point	:	Not available
Freezing point	:	Not available
Boiling point	:	Not available
Flammability	:	Not available
Explosive limits	:	Not available
Lower explosive limit (LEL)	:	Not available
Upper explosive limit (UEL)	:	Not available
Flash point	:	Not applicable
Auto-ignition temperature	:	Not available
Decomposition temperature	:	Not available
рН	:	Not available
Viscosity, kinematic	:	Not available
Solubility	:	Not available
Partition coefficient n-octanol/water (Log Kow)	:	Not available
Vapour pressure	:	Not available

KSD2

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Vapour pressure at 50°C	:	Not available
Density	:	Not available
Relative density	:	0.6
Relative vapour density at 20°C	:	Not available
Particle size	:	Not applicable
Particle size distribution	:	Not applicable
Particle shape	:	Not applicable
Particle aspect ratio	:	Not applicable
Particle aggregation state	:	Not applicable
Particle agglomeration state	:	Not applicable
Particle specific surface area	:	Not applicable
Particle dustiness	:	Not applicable

9.2. Other information

9.2.1. Information with regard to physical hazard classes

% of flammable ingredients

: 91.45011738

9.2.2. Other safety characteristics

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Pressurised container: May burst if heated.

10.2. Chemical stability
Stable under normal conditions.

10.3. Possibility of hazardous reactions

No additional information available

10.4. Conditions to avoid

Direct sunlight. Heat. Open flame.

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

No additional information available

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral)	:	Not classified
Acute toxicity (dermal)	:	Not classified
Acute toxicity (inhalation)	:	Not classified
Skin corrosion/irritation	:	Not classified
Serious eye damage/irritation	:	Causes serious eye irritation.
Respiratory or skin sensitisation	:	Not classified
Germ cell mutagenicity	:	Not classified
Carcinogenicity	:	Not classified
Reproductive toxicity	:	Not classified
STOT-single exposure	:	Not classified

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

propan-2-ol; isopropyl alcohol; isopropanol		
STOT-single exposure	May cause drowsiness or dizziness.	
STOT-repeated exposure	Not classified	
Aspiration hazard	: Not classified	
Vaporizer	Aerosol	
11.2. Information on other hazards		

No additional information available

SECTION 12: Ecological information		
12.1. Toxicity		
Hazardous to the aquatic environment, short-term : Not classified (acute) Hazardous to the aquatic environment, long-term : Harmful to aquatic life with long lasting effects. (chronic)		
propan-2-ol; isopropyl alcohol; isopropanol (6	57-63-0)	
LC50 - Fish [1]	9640 mg/l	
EC50 - Other aquatic organisms [1]	13299 mg/l waterflea	
EC50 - Other aquatic organisms [2] > 1000 mg/l		
12.2. Persistence and degradability		
No additional information available		
12.3. Bioaccumulative potential		
propan-2-ol; isopropyl alcohol; isopropanol (67-63-0)		
Partition coefficient n-octanol/water (Log Pow) 0.05		
12.4. Mobility in soil		
No additional information available		
12.5. Results of PBT and vPvB assessment		
No additional information available		
12.6. Endocrine disrupting properties		
No additional information available		
12.7. Other adverse effects		
No additional information available		

SECTION 13: Disposal considerations	
13.1. Waste treatment methods	
Product/Packaging disposal recommendations	: Do not pierce or burn, even after use.

SECTION 14: Transport information	
In accordance with ADR / IMDG / IATA	

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

14.1. UN number or ID number	
UN-No. (ADR) UN-No. (IMDG) UN-No. (IATA)	: UN 1950 : UN 1950 : UN 1950
14.2. UN proper shipping name	
Proper Shipping Name (ADR) Proper Shipping Name (IMDG) Proper Shipping Name (IATA) Transport document description (ADR) Transport document description (IMDG) Transport document description (IATA)	 AEROSOLS AEROSOLS Aerosols, flammable UN 1950 AEROSOLS, 2.1, (D) UN 1950 AEROSOLS, 2.1 UN 1950 Aerosols, flammable, 2.1
14.3. Transport hazard class(es)	
ADR Transport hazard class(es) (ADR) Danger labels (ADR)	: 2.1 : 2.1 :
IMDG Transport hazard class(es) (IMDG) Danger labels (IMDG)	: 2.1 : 2.1 :
IATA Transport hazard class(es) (IATA) Danger labels (IATA)	: 2.1 : 2.1 :
14.4. Packing group	•
Packing group (ADR) Packing group (IMDG) Packing group (IATA)	 Not applicable Not applicable Not applicable
14.5. Environmental hazards	
Dangerous for the environment Marine pollutant Other information	: No : No : No supplementary information available
14.6. Special precautions for user	
Overland transport Classification code (ADR) Special provisions (ADR) Limited quantities (ADR) Excepted quantities (ADR) Packing instructions (ADR) Special packing provisions (ADR) Mixed packing provisions (ADR)	: 5F : 190, 327, 344, 625 : 1I : E0 : P207, LP200 : PP87, RR6, L2 : MP9
Document generated @ 27/04/2024 18:12:35	- Page 9 o

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Transport category (ADR)	: 2
Special provisions for carriage - Packages (ADR)	: V14
Special provisions for carriage - Loading, unloading	: CV9, CV12
and handling (ADR)	
Special provisions for carriage - Operation (ADR)	: S2
Tunnel restriction code (ADR)	: D
Transport by sea	
Special provisions (IMDG)	: 63, 190, 277, 327, 344, 381, 959
Limited quantities (IMDG)	: SP277
Excepted quantities (IMDG)	: E0
Packing instructions (IMDG)	: P207, LP200
Special packing provisions (IMDG)	: PP87, L2
EmS-No. (Fire)	: F-D
EmS-No. (Spillage)	: S-U
Stowage category (IMDG)	: None
Air transport	
PCA Excepted quantities (IATA)	: E0
PCA Limited quantities (IATA)	: Y203
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 203
PCA max net quantity (IATA)	: 75kg
CAO packing instructions (IATA)	: 203
CAO max net quantity (IATA)	: 150kg
Special provisions (IATA)	: A145, A167, A802
ERG code (IATA)	: 10L
14.7 Maritime transport in bulk according t	o IMO instruments

14.7. Maritime transport in bulk according to IMO instruments

IBC code

: Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no substance(s) listed on REACH Annex XVII (Restriction Conditions)

Contains no substance(s) listed on the REACH Candidate List

Contains no substance(s) listed on REACH Annex XIV (Authorisation List)

Contains no substance(s) listed on the PIC list (Regulation EU 649/2012 concerning the export and import of hazardous chemicals)

Contains no substance(s) listed on the POP list (Regulation EU 2019/1021 on persistent organic pollutants)

Contains no substance(s) listed on the Explosives Precursors list (Regulation EU 2019/1148 on the marketing and use of explosives precursors)

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No additional information available

SECTION 16: Other information

Full text of H- and EUH-statements:		
Aquatic Acute 1 Hazardous to the aquatic environment – Acute Hazard, Category 1		
Aquatic Chronic 1 Hazardous to the aquatic environment – Chronic Hazard, Category 1		
EUH208	Contains Benzyl salicylate, (R)-p-mentha-1,8-diene; d-limonene. May produce an allergic reaction.	
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2	

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Full text of H- and EUH-statements:			
Flam. Gas 1A	Flammable gases, Category 1A		
Flam. Liq. 2	Flammable liquids, Category 2		
Flam. Liq. 3	Flammable liquids, Category 3		
H220	Extremely flammable gas.		
H222	Extremely flammable aerosol.		
H225	Highly flammable liquid and vapour.		
H226	26 Flammable liquid and vapour.		
H229	Pressurised container: May burst if heated.		
H315	Causes skin irritation.		
H317	May cause an allergic skin reaction.		
H319	Causes serious eye irritation.		
H336	May cause drowsiness or dizziness.		
H400	H400 Very toxic to aquatic life.		
H410	Very toxic to aquatic life with long lasting effects.		
H412	Harmful to aquatic life with long lasting effects.		
Press. Gas	Gases under pressure		
Skin Irrit. 2	Skin corrosion/irritation, Category 2		
Skin Sens. 1	S. 1 Skin sensitisation, Category 1		
STOT SE 3	Specific target organ toxicity – Single exposure, Category 3, Narcosis		

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Aerosol 1	H222;H229	On basis of test data
Eye Irrit. 2	H319	Calculation method
Aquatic Chronic 3	H412	Calculation method

Safety Data Sheet (SDS), EU

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.